

Pemco Never-Flat PF Polyurethane Foam Casters & Wheels


The era of
flat tires
is over!

Solid cushion micro-cellular polyurethane tire has similar rollability characteristics as a pneumatic tire... but they never go flat.

- No more flats
- No air nozzles or air compressors
- No tire pressure maintenance
- No downtime from punctures or blowouts

Additional benefits:

- Reduced maintenance costs
- Cushion non-marking floor protection
- Smooth impact resistant ride even on uneven terrain
- Soft polyurethane tread resistant to harsh chemicals compared to rubber



Pemco Never-Flat Tires **NEVER GO FLAT**



Increased productivity
Reduced maintenance costs
Protecting your equipment



Pemco Never-Flat PF



Caster Features

- Weight capacities to 350 lbs.
- Sealed upper raceway keeps out dirt & debris
- Double ball raceways for smooth swiveling action
- Zerk fitting in swivel raceway for easy maintenance
- 3/16" thick steel leg construction
- 5/8" diameter kingpin
- RoHS compliant industrial zinc finish for corrosion resistance

Pemco Never-Flat™ PF casters never go flat! The wheels feature a unique open and closed micro cellular polyurethane technology. Pemco Never-Flat™ PF provides the greatest possible protection to both load and floor for both on-road and off-road applications. The casters also feature sealed raceways for extra protection against the elements.


Wheel Features

- Unique open and closed micro-cellular polyurethane wheel technology
- Acts just like a pneumatic tire ... but will never go flat
- Shock absorbing wheels provide ultimate cargo and floor protection
- Quiet, smooth mobility
- Painted hubs for extra protection
- Zerk fitting for easy axle maintenance
- Sealed precision ball bearings standard
- Durometer: 80A ±5



Caster Models and Specifications

Nominal Wheel Diameter	Tread Width	Wheel Type	Bearing	Load Capacity (lbs)	Mount Height	Swivel Radius	Swivel Caster Part #	Swivel Caster With Cam Brake Part #	Rigid Caster Part #
8"	2.80"	2.80/2.50-4	Precision Ball	275	10"	6-1/4"	NFPF80SWL	NFPF80SWLB	NFPF80RGD
10"	4.10"	4.10/3.50-4	Precision Ball	300	12"	7-1/2"	NFPF10SWL	NFPF10SWLB	NFPF10RGD
12"	4.10"	4.10/3.50-6	Precision Ball	350	15-3/8"	9-1/4"	NFPF12SWL	NFPF12SWLB	NFPF12RGD



Top plate bolt hole pattern

No-matic Wheel Models and Specifications

Nominal Wheel Diameter	Tread Width	Wheel Type	Bearing	Load Capacity (lbs)	Bearing ID	Hub Length	Wheel Part #
8"	2.80"	2.80/2.50-4	Precision Ball	275	5/8"	3-7/8"	WH8X2.5NFPPF
10"	4.10"	4.10/3.50-4	Precision Ball	300	5/8"	3-7/8"	WH10X3.5NFPPF
12"	4.10"	4.10/3.50-6	Precision Ball	350	5/8"	4-5/16"	WH12X3.5NFPPF



WH10X3.5EZ



WH10X3.5NFPPFOFF

Handtruck Wheel: Offset 1-piece hub

Nominal Wheel Diameter	Tread Width	Wheel Type	Bearing	Load Capacity (lbs)	Bearing ID	Hub Length	Wheel Part #
10"	4.10"	4.10/3.50-4	Precision Ball	300	5/8"	2-1/4"	WH10X3.5NFPPFOFF

Pemco

A Brand of Colson Group
Phone: 800-253-0868